

- Available in LED, Incandescent & GU24
- Molded of Durable Non-Corrosive UV Resistant Resins
- Knockouts for Conduit
- Wall or Ceiling Mount
- UL Listed for Wet Locations
- Standard Pack QTY: 12



RoHS compliant



EXAMPLE # FK395-LE1200C-BWM

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FK391 FK395	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR LE800 - 13W Power Input W-900lm 3000K CRI 80 (TYP) C-1000lm 4000K >65 Lumens Per Watt**	W-White B- Black	POLYCARBONATE F-Frosted Prismatic W-White	M-Motion Sensor
	LE1200 - 14W Power Input W-1350lm 3000K CRI 80 (TYP) C-1400lm 4000K >80 Lumens Per Watt**			
	LE1800 - 23W Power Input W-1850lm 3000K CRI 80 (TYP) C-1900lm 4000K >80 Lumens Per Watt**			
	MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY, ENERGY STAR L1800 - 22W Power Input C-1824lm 4000K CRI 74 (TYP) >82 Lumens Per Watt**	W-White B- Black	POLYCARBONATE F-Frosted Prismatic W-White	M-Motion Sensor
	INCANDESCENT, MEDIUM BASE, 120V I240-2 X 40W Max	W-White B- Black	POLYCARBONATE F-Frosted Prismatic W-White	LED LAMP, 3 YEAR WARRANTY, DIMMABLE ENERGY STAR LWE-A19/E26, 2700K LCE-A19/E26, 4000K
	GU24 BASE, 120V G13-1 X 13W G213- 2 X 13W G18-1 X 18W G218- 2 X 18W	W-White B-Black	POLYCARBONATE F-Frosted Prismatic W-White	L-CFL, 2700K



*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE

Scan the QR code to the left to access the Energy Star qualified product list.

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.