


- Available in LED, Incandescent & GU24
- Molded of Durable Non-Corrosive UV Resistant Resins
- Wall Mount Only
- UL Listed for Wet Locations
- Standard Pack QTY: 1



EXAMPLE # FN151-I60-BW-PLWE

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FN151	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C, TO +40°C 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR	W-White B- Black	ACRYLIC C-Clear Prism W-White	P-Photocell
	LE800 - 13W Power Input CRI 80 (TYP) >65 Lumens Per Watt**	W-900lm 3000K C-1000lm 4000K		
	MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED ARRAY, 50,000 HRS L70* AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY, ENERGY STAR	W-White B- Black	ACRYLIC W-White	P-Photocell (120V only)
	L900 - 11.3W Power Input CRI 74 (TYP) >80 Lumens Per Watt**	C-912lm 4000K		
INCANDESCENT, MEDIUM BASE, 120V I60-1 X 60W	W-White B- Black	POLYCARBONATE C-Clear Prism W-White	P-Photocell LED LAMP, 3 YEAR WARRANTY, DIMMABLE ENERGY STAR LWE-A19/E26, 2700K LCE-A19/E26, 4000K	
GU24 BASE, 120V G13-1 X 13W G18-1 X 18W G23-1 X 23W	W-White B- Black	ACRYLIC C-Clear Prism W-White	L-CFL, 2700K	



*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE

Scan the QR code to the left to access the Energy Star qualified product list.

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.

For more information contact our sales department at 1-800-325-7364 or visit www.interglobal-inc.com