


- Available in LED, Incandescent & GU24
- Molded of Durable Non-Corrosive UV Resistant Resins
- Fits Most 3" Diameter Posts
- UL Listed for Wet Locations
- Standard Pack QTY: 1

NAUTICAL



FN253



RoHS compliant

EXAMPLE # FN253-LE800C-BCP

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FN253	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE LE800 - 13W Power Input CRI 80 (TYP) >65 Lumens Per Watt** W-900lm 3000K C-1000lm 4000K	W-White B- Black	POLYCARBONATE C-Clear Prism	N/A
	INCANDESCENT, MEDIUM BASE, 120V I60-1 X 60W	W-White B- Black	POLYCARBONATE C-Clear Prism	LED LAMP, 3 YEAR WARRANTY, DIMMABLE LWE-A19/E26, 2700K LCE-A19/E26, 4000K
	GU24 BASE, 120V G13-1 X 13W G18-1 X 18W G23-1 X 23W	W-White B- Black	POLYCARBONATE C-Clear Prism	L-CFL, 2700K

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.