


- Available in LED & GU24
- Molded of Durable Non-Corrosive UV Resistant Resins with Powder Coated Aluminum Base
- Wall or Ceiling Mount
- UL Listed for Wet Locations
- Standard Pack QTY: 12


COMMERCIAL EUROSTYLE



FE363



HCMT: 5 1/4"



EXAMPLE # FE363-G13-BFPL

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS	
FE363	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR	W-White B- Black	POLYCARBONATE F-Frosted	P-Photocell	
	LE800 - 13W Power Input CRI 80 (TYP) >65 Lumens Per Watt**				W-900lm 3000K C-1000lm 4000K
	LE1200 - 14W Power Input CRI 80 (TYP) >80 Lumens Per Watt**				W-1350lm 3000K C-1400lm 4000K
FE363	MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED ARRAY, 50,000 HRS L70* AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY, ENERGY STAR	W-White B- Black	POLYCARBONATE F-Frosted	P-Photocell	
	L1800 - 22W Power Input CRI 74 (TYP) >82 Lumens Per Watt**				C-1824lm 4000K
FE363	GU24 BASE, 120V G13-1 X 13W G213- 2 X 13W G18-1 X 18W G218- 2 X 18W G23-1 X 23W G26-1 X 26W or 27W	W-White B-Black	POLYCARBONATE F-Frosted	P-Photocell L-CFL, 2700K	



*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE

Scan the QR code to the left to access the Energy Star qualified product list.

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.

For more information contact our sales department at 1-800-325-7364 or visit www.interglobal-inc.com