


- Available in LED, Incandescent & GU24
- Molded of Durable Non-Corrosive UV Resistant Resins with Polycarbonate Base
- Ceiling Mount
- UL Listed for Damp Locations
- Standard Pack QTY: 6

RESIDENTIAL CENTURY - 10.25"



FC312



EXAMPLE # FC312-G13-BFL

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FC312	INCANDESCENT, MEDIUM BASE, 120V I260-2 X 60W	W-White B- Black	POLYPROPYLENE F-Frosted GLASS G-Clear	LED LAMP, 3 YEAR WARRANTY DIMMABLE, ENERGY STAR LWE-A19/E26, 2700K LCE-A19/E26, 4000K
	GU24 BASE, 120V G13-1 X 13W G213-2 X 13W G18-1 X 18W G218-2 X 18W G23-1 X 23W G223- 2 X 23W G26-1 X 26W or 27W	W-White B- Black	POLYPROPYLENE F-Frosted GLASS G-Clear	L-CFL, 2700K

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE



Scan the QR code to the left to access the Energy Star qualified product list.

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.

For more information contact our sales department at 1-800-325-7364 or visit www.interglobal-inc.com