


- Available in LED & GU24
- Molded of Durable Non-Corrosive UV Resistant Resins with Aluminum Base
- Ceiling Mount
- UL Listed for Damp Locations
- Standard Pack QTY: 6

COMMERCIAL CENTURY - 8.25"



FC321



EXAMPLE # FC321-LE800C-BFP

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS	
FC321	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR	W-White B- Black	POLYPROPYLENE F-Frosted GLASS G-Clear	P-Photocell	
	LE800 - 13W Power Input CRI 80 (TYP) >65 Lumens Per Watt**				W-900lm 3000K C-1000lm 4000K
	LE1200 - 14W Power Input CRI 80 (TYP) >80 Lumens Per Watt**				W-1350lm 3000K C-1400lm 4000K
FC321	MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED ARRAY, 50,000 HRS L70* AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY, ENERGY STAR	W-White B- Black	POLYPROPYLENE F-Frosted GLASS G-Clear	P-Photocell	
	L900 - 11.3W Power Input CRI 74 (TYP) >80 Lumens Per Watt**				C-912lm 4000K
FC321	GU24 BASE, 120V G13-1 X 13W G18-1 X 18W G23-1 X 23W G26-1 X 26W or 27W	W-White B-Black	POLYPROPYLENE F-Frosted GLASS G-Clear	P- Photocell L-CFL, 2700K	

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE



Scan the QR code to the left to access the Energy Star qualified product list.

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.