


- Available in LED & GU24
- Molded of Durable Non-Corrosive UV Resistant Resins with Aluminum Base
- Ceiling Mount
- UL Listed for Damp Locations
- Standard Pack QTY: 6

COMMERCIAL CENTURY - 10.25"



FC322



EXAMPLE # FC322-G13-BFPL

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS	
FC322	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR	W -White B - Black	P OLYPROPYLENE F -Frosted G LASS G -Clear	M -Motion Sensor P -Photocell	
	LE800 - 13W Power Input CRI 80 (TYP) >65 Lumens Per Watt**				W -900lm 3000K C -1000lm 4000K
	LE1200 - 14W Power Input CRI 80 (TYP) >80 Lumens Per Watt**				W -1350lm 3000K C -1400lm 4000K
	LE1800 - 23W Power Input CRI 80 (TYP) >80 Lumens Per Watt**				W -1850lm 3000K C -1900lm 4000K
FC322	MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED ARRAY, 50,000 HRS L70* AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY, ENERGY STAR	W -White B - Black	P OLYPROPYLENE F -Frosted G LASS G -Clear	M -Motion Sensor P -Photocell (120V only)	
	L1800 - 22W Power Input CRI 74 (TYP) >82 Lumens Per Watt**				C -1824lm 4000K
FC322	GU24 BASE, 120V	W -White B -Black	P OLYPROPYLENE F -Frosted G LASS G -Clear	P - Photocell L -CFL, 2700K	
	G13 -1 X 13W				
	G213 - 2 X 13W				
	G18 -1 X 18W				
	G218 - 2 X 18W				
	G23 -1 X 23W				
G223 -2 X 23W					
G26 -1 X 26W or 27W					



*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE

Scan the QR code to the left to access the Energy Star qualified product list.

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.

For more information contact our sales department at 1-800-325-7364 or visit www.interglobal-inc.com