

- Available in LED, Incandescent & GU24
- Molded of Durable Non-Corrosive UV Resistant Resins
- Wall Mount Only
- UL Listed for Wet Locations
- Standard Pack QTY: 3



EXAMPLE # FR101-LE800C-BCP

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FR101 FR102 FR103	<p>EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR</p> <p>LE800-13W Power Input CRI 80 (TYP) >65 Lumens Per Watt**</p> <p>W-900lm 3000K C-1000lm 4000K</p>	<p>W-White B-Black</p>	<p>ACRYLIC C-Clear F-Glare Free Frost</p>	<p>P-Photocell</p>
	<p>INCANDESCENT, MEDIUM BASE, 120V I60-1 X 60W Max</p>	<p>W-White B-Black</p>	<p>ACRYLIC C-Clear F-Glare Free Frost</p>	<p>P-Photocell LED LAMP, 3 YEAR WARRANTY DIMMABLE, ENERGY STAR LWE-A19/E26, 2700K LCE-A19/E26, 4000K</p>
	<p>GU24 BASE, 120V G13-1 X 13W G18-1 X 18W G23-1 X 23W</p>	<p>W-White B-Black</p>	<p>ACRYLIC C-Clear F-Glare Free Frost</p>	<p>P-Photocell L-CFL, 2700K</p>

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE



Scan the QR code to the left to access the Energy Star qualified product list.

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.

For more information contact our sales department at 1-800-325-7364 or visit www.interglobal-inc.com