


- Available in LED, Incandescent & GU24
- Molded of Durable Non-Corrosive UV Resistant Resins
- Fits Most 3" Diameter Posts
- UL Listed for Wet Locations
- Standard Pack QTY: 1

### CAMBRIDGE POST



**FC259**



RoHS compliant

#### EXAMPLE # FC259-I60-BC-LCE

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
<b>FC259</b>	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE <b>LE800</b> -13W Power Input CRI 80 (TYP) >65 Lumens Per Watt**	<b>W</b> -White <b>B</b> -Black	<b>ACRYLIC</b> <b>C</b> -Clear	N/A
	INCANDESCENT, MEDIUM BASE, 120V <b>I60</b> -1 X 60W Max	<b>W</b> -White <b>B</b> -Black	<b>ACRYLIC</b> <b>C</b> -Clear	LED LAMP, 3 YEAR WARRANTY, DIMMABLE <b>LWE</b> -A19/E26, 2700K <b>LCE</b> -A19/E26, 4000K
	GU24 BASE, 120V <b>G13</b> -1 X 13W <b>G18</b> -1 X 18W <b>G23</b> -1 X 23W <b>G26</b> -1 X 26W or 27W	<b>W</b> -White <b>B</b> -Black	<b>ACRYLIC</b> <b>C</b> -Clear	L-CFL, 2700K

\*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

\*\*ESTIMATED FROM LED SOURCE

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.