


- Available in LED, Incandescent & GU24
- Molded of Durable Non-Corrosive UV Resistant Resins
- Fits Most 3" Diameter Posts
- UL Listed for Wet Locations
- Standard Pack QTY: 1

GLASS CHIMNEY POST



FT271



RoHS compliant

EXAMPLE # FT271-LE800C-BCGT

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FT271	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE LE800 -13W Power Input W -900lm 3000K CRI 80 (TYP) C -1000lm 4000K >65 Lumens Per Watt**	B -Black	ACRYLIC C -Clear F - Glare Free Frost	G - Glass Chimney Frosted T - Brass Finial
	INCANDESCENT, MEDIUM BASE, 120V I75 -1 X 75W Max	B -Black	ACRYLIC C -Clear F - Glare Free Frost	G - Glass Chimney Frosted T -Brass Finial LED LAMP, 3 YEAR WARRANTY DIMMABLE LW -A19/E26, 2700K LC -A19/E26, 4000K
	GU24 BASE, 120V G13 -1 X 13W G18 -1 X 18W G23 -1 X 23W G26 -1 X 26W or 27W	B -Black	ACRYLIC C -Clear F - Glare Free Frost	G - Glass Chimney Frosted T -Brass Finial L -CFL, 2700K

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.