

- Available in LED, Incandescent & GU24
- Fade & Rust Resistant Composite Construction
- Wall Mount Only
- UL Listed for Wet Locations
- Standard Pack QTY: 3

HATCH WALL



EXAMPLE # FR111-I60-BC-PLWE

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FR111 FR112 FR113	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR	W-White B-Black	ACRYLIC C-Clear F-Frost	P-Photocell
	LE800 - 13W, 80 CRI >88 Lumens Per Watt**	W-1140lm 3000K C-1280lm 4000K		
	INCANDESCENT, MEDIUM BASE, 120V I60-1 X 60W Max	W-White B-Black	ACRYLIC C-Clear F-Frost	P-Photocell LED LAMP, 3 YEAR WARRANTY, DIMMABLE, ENERGY STAR LWE-A19/E26, 80CRI, 3000K LCE-A19/E26, 80CRI, 4000K
	GU24 BASE, 120V G13-1 X 13W G18-1 X 18W	W-White B-Black	ACRYLIC C-Clear F-Frost	P-Photocell L-CFL, 2700K

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE



Scan the QR code to the left to access the Energy Star qualified product list.

90CRI OPTIONS AVAILABLE - SEE PAGE 112 FOR DIMMER COMPATIBILITY

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.