



- Available in LED, Incandescent & GU24
- Fade & Rust Resistant Composite Construction
- Wall Mount Only
- UL Listed for Wet Locations
- Standard Pack QTY: 1

CAMBRIDGE WALL






FC159

EXTENDS: 9"
HCMT: 12 1/4"




FC160

EXTENDS: 9"
HCMT: 12 1/4"

RoHS compliant



ASK ABOUT ENERGY STAR

EXAMPLE # FC159-LE800C-BCP

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FC159 FC160	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR LE800 - 13W, 80 CRI >88 Lumens Per Watt**	W -White B -Black	ACRYLIC C -Clear	P -Photocell
	INCANDESCENT, MEDIUM BASE, 120V I60-1 X 60W Max	W -White B -Black	ACRYLIC C -Clear	P -Photocell LED LAMP, 3 YEAR WARRANTY, DIMMABLE, ENERGY STAR LWE -A19/E26, 80CRI, 3000K LCE -A19/E26, 80CRI, 4000K
	GU24 BASE, 120V G13 -1 X 13W G18 -1 X 18W G26 -1 X 27W	W -White B -Black	ACRYLIC C -Clear	P -Photocell L -CFL, 2700K

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE



Scan the QR code to the left to access the Energy Star qualified product list.

90CRI OPTIONS AVAILABLE - SEE PAGE 112 FOR DIMMER COMPATIBILITY

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.