


- Available in LED, Incandescent & GU24
- Fade & Rust Resistant Composite Construction
- Fits Most 3" Diameter Posts
- UL Listed for Wet Locations
- Standard Pack QTY: 1

CAMBRIDGE POST



FC259



RoHS compliant

EXAMPLE # FC259-I60-BC-LCE

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FC259	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70+, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE LE800 - 13W, 80 CRI W -1140lm 3000K >88 Lumens Per Watt** C -1280lm 4000K	W -White B -Black	ACRYLIC C -Clear	N/A
	INCANDESCENT, MEDIUM BASE, 120V I60-1 X 60W Max	W -White B -Black	ACRYLIC C -Clear	LED LAMP, 3 YEAR WARRANTY, DIMMABLE LWE -A19/E26, 80CRI, 3000K LCE -A19/E26, 80CRI, 4000K
	GU24 BASE, 120V G13 -1 X 13W G18 -1 X 18W G26 -1 X 27W	W -White B -Black	ACRYLIC C -Clear	L -CFL, 2700K

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE

90CRI OPTIONS AVAILABLE - SEE PAGE 112 FOR DIMMER COMPATIBILITY

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.