


- Available in LED, Incandescent & GU24
- Fade & Rust Resistant Composite Construction
- Fits Most 3" Diameter Posts
- UL Listed for Wet Locations
- Standard Pack QTY: 6

## PRINCETON POST



FP221



RoHS compliant

### EXAMPLE # FP221-I60-BC-LWE

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FP221	<b>EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE</b> <b>LE800</b> - 13W, 80 CRI <b>W-1140lm 3000K</b> >88 Lumens Per Watt** <b>C-1280lm 4000K</b>	<b>W-White</b> <b>B-Black</b>	<b>ACRYLIC</b> <b>C-Clear</b> <b>W-White</b>	N/A
	<b>INCANDESCENT, MEDIUM BASE, 120V</b> <b>I60-1 X 60W Max</b>	<b>W-White</b> <b>B-Black</b>	<b>ACRYLIC</b> <b>C-Clear</b> <b>W-White</b>	<b>LED LAMP, 3 YEAR WARRANTY, DIMMABLE</b> <b>LWE-A19/E26, 80CRI, 3000K</b> <b>LCE-A19/E26, 80CRI, 4000K</b>
	<b>GU24 BASE, 120V</b> <b>G13-1 X 13W</b> <b>G18-1 X 18W</b> <b>G26-1 X 27W</b>	<b>W-White</b> <b>B-Black</b>	<b>ACRYLIC</b> <b>C-Clear</b> <b>W-White</b>	L-CFL, 2700K

\*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

\*\*ESTIMATED FROM LED SOURCE

90CRI OPTIONS AVAILABLE - SEE PAGE 112 FOR DIMMER COMPATIBILITY

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.