



- Available in LED, Incandescent & GU24
- Fade & Rust Resistant Composite Construction
- Wall Mount Only
- UL Listed for Wet Locations
- Standard Pack QTY: 1

## AMHERST WALL






**FA182**

7 3/4"  
25"  
EXTENDS: 9"  
HCMT: 15 5/8"




**FA183**

7 3/4"  
19 5/8"  
EXTENDS: 9"  
HCMT: 15 5/8"

RoHS compliant



### EXAMPLE # FA182-LE800C-BWP

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FA182 FA183	<b>EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR</b>  <b>LE800</b> - 13W, 80 CRI <b>W-1140lm 3000K</b> >88 Lumens Per Watt** <b>C-1280lm 4000K</b>	<b>W-White</b> <b>B-Black</b>	<b>ACRYLIC</b> <b>C-Clear</b> <b>W-White</b> <b>F- Glare Free Frost</b>	<b>P-Photocell</b>
	<b>INCANDESCENT, MEDIUM BASE, 120V</b> <b>I75- 1 X 75W Max</b>	<b>W-White</b> <b>B-Black</b>	<b>ACRYLIC</b> <b>C-Clear</b> <b>W-White</b> <b>F- Glare Free Frost</b>	<b>P-Photocell</b>  <b>LED LAMP, 3 YEAR WARRANTY, DIMMABLE, ENERGY STAR</b> <b>LWE-A19/E26, 80CRI, 3000K</b> <b>LCE-A19/E26, 80CRI, 4000K</b>
	<b>GU24 BASE, 120V</b> <b>G13-1 X 13W</b> <b>G18-1 X 18W</b> <b>G26-1 X 27W</b>	<b>W-White</b> <b>B-Black</b>	<b>ACRYLIC</b> <b>C-Clear</b> <b>W-White</b> <b>F- Glare Free Frost</b>	<b>P-Photocell</b> <b>L-CFL, 2700K</b>

\*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

\*\*ESTIMATED FROM LED SOURCE



Scan the QR code to the left to access the Energy Star qualified product list.

**90CRI OPTIONS AVAILABLE - SEE PAGE 112 FOR DIMMER COMPATIBILITY**

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.