


- Available in LED, Incandescent & GU24
- Fade & Rust Resistant Composite Construction
- Wall Mount Only
- UL Listed for Wet Locations
- Standard Pack QTY: 1

### LARGE TUDOR WALL



SHOWN WITH OPTIONAL DECORATIVE CHIMNEY

FT171



EXTENDS: 10 1/4"  
HCMT: 15"



RoHS compliant



#### EXAMPLE # FT171-I75-BC-GTLWE

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FT171	<p><b>EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR</b></p> <p><b>LE800</b> - 13W, 80 CRI    <b>W-1140lm 3000K</b>                      &gt;88 Lumens Per Watt**    <b>C-1280lm 4000K</b></p>	B-Black	<p><b>ACRYLIC</b>  <b>C</b>-Clear  <b>F</b>- Glare Free Frost</p>	<p><b>C</b>- Decorative Chimney  <b>T</b>- Brass Finial</p>
	<p><b>INCANDESCENT, MEDIUM BASE, 120V</b>  <b>I75-1 X 75W Max</b></p>	B-Black	<p><b>ACRYLIC</b>  <b>C</b>-Clear  <b>F</b>- Glare Free Frost</p>	<p><b>G</b>-Decorative Chimney  <b>T</b>-Brass Finial  <b>LED LAMP, 3 YEAR WARRANTY, DIMMABLE, ENERGY STAR</b>  <b>LWE-A19/E26, 80CRI, 3000K</b>  <b>LCE-A19/E26, 80CRI, 4000K</b></p>
	<p><b>GU24 BASE, 120V</b>  <b>G13-1 X 13W</b>  <b>G18-1 X 18W</b>  <b>G26-1 X 27W</b></p>	B-Black	<p><b>ACRYLIC</b>  <b>C</b>-Clear  <b>F</b>- Glare Free Frost</p>	<p><b>G</b>-Decorative Chimney  <b>T</b>-Brass Finial  <b>L</b>-CFL, 2700K</p>

\*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

\*\*ESTIMATED FROM LED SOURCE



Scan the QR code to the left to access the Energy Star qualified product list.

90CRI OPTIONS AVAILABLE - SEE PAGE 112 FOR DIMMER COMPATIBILITY

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.