

- Available in LED, Incandescent & GU24
- Fade & Rust Resistant Composite Construction
- Fits Most 3" Diameter Posts
- UL Listed for Wet Locations
- Standard Pack QTY: 1

GLOBES



FG212





FG214



FG216







RoHS compliant

EXAMPLE # FG214-I150-BW-LWE

STYLE #	LIGHT SOURCE	BODY	GLOBE	OPTIONS
FG212	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE LE800 - 13W, 80 CRI >88 Lumens Per Watt** W -1140lm 3000K C -1280lm 4000K	W -White B - Black	ACRYLIC C -Clear Prism W -White	N/A
	INCANDESCENT, MEDIUM BASE, 120V I100-1 X 100W	W -White B - Black	ACRYLIC C -Clear Prism W -White	LED LAMP, 3 YEAR WARRANTY, DIMMABLE LWE -A19/E26, 80CRI, 3000K LCE -A19/E26, 80CRI, 4000K
	GU24 BASE, 120V G13-1 X 13W G18-1 X 18W G26-1 X 27W	W -White B - Black	ACRYLIC C -Clear Prism W -White	L-CFL, 2700K
FG214 FG216	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE LE800 - 13W, 80 CRI >88 Lumens Per Watt** W -1140lm 3000K C -1280lm 4000K	W -White B - Black	ACRYLIC C -Clear Prism W -White	N/A
	INCANDESCENT, MEDIUM BASE, 120V I150-1 X 150W	W -White B - Black	ACRYLIC C -Clear Prism W -White	LED LAMP, 3 YEAR WARRANTY, DIMMABLE LWE -A19/E26, 80CRI, 3000K LCE -A19/E26, 80CRI, 4000K
	GU24 BASE, 120V G13-1 X 13W G18-1 X 18W G26-1 X 27W	W -White B - Black	ACRYLIC C -Clear Prism W -White	L-CFL, 2700K

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST **ESTIMATED FROM LED SOURCE

90CRI OPTIONS AVAILABLE - SEE PAGE 112 FOR DIMMER COMPATIBILITY


Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.

- Available in LED, Incandescent & GU24
- Fade & Rust Resistant Composite Construction
- Fits Most 3" Diameter Posts
- UL Listed for Wet Locations
- Standard Pack QTY: 1

10" GLOBE



FG210



RoHS
compliant

EXAMPLE # FG210-I100-BW-LWE

STYLE #	LIGHT SOURCE	BODY	GLOBE	OPTIONS
FG210	INCANDESCENT, MEDIUM BASE, 120V I100-1 X 100W	W-White B- Black	ACRYLIC C-Clear Prism W-White	LED LAMP, 3 YEAR WARRANTY, DIMMABLE LWE-A19/E26, 80CRI, 3000K LCE-A19/E26, 80CRI, 4000K
	GU24 BASE, 120V G13-1 X 13W G18-1 X 18W G26-1 X 27W	W-White B- Black	ACRYLIC C-Clear Prism W-White	L-CFL, 2700K

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE

SEE PAGE 112 FOR DIMMER COMPATIBILITY

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.

For more information contact our sales department at 1-800-325-7364 or visit www.interglobal-inc.com