- Available in LED, Incandescent & GU24
- Fade & Rust Resistant Composite Construction
- Fits Most 3" Diameter Posts
- UL Listed for Wet Locations
- Standard Pack QTY: 1

ACORNS

FA201



FA202



LED

MADE IN USA

c UL us

RoHS compliant

EXAMPLE # FA201-G13-BCL

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FA201 **FA202**	**EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40˚C TO +40˚C, 5 YEAR WARRANTY, DIMMABLE** **LE800** - 13W, 80 CRI >88 Lumens Per Watt** **W**-1140lm 3000K **C**-1280lm 4000K **LE1200** - 14W, 80 CRI >102 Lumens Per Watt** **W**-1430lm 3000K **C**-1500lm 4000K **LE1800** - 22W, 80 CRI >88 Lumens Per Watt** **W**-1950lm 3000K **C**-2130lm 4000K	**W**-White **B**- Black	**ACRYLIC** **A**-Clear Textured **POLYCARBONATE** **C**-Clear Textured **POLYETHYLENE** **W**-White Textured	N/A
	INCANDESCENT, MEDIUM BASE, 120V **I150**-1 X 150W Max	**W**-White **B**- Black	**ACRYLIC** **A**-Clear Textured **POLYCARBONATE** **C**-Clear Textured **POLYETHYLENE** **W**-White Textured	**LED LAMP, 3 YEAR WARRANTY, DIMMABLE** **LWE**-A19/E26, 80CRI, 3000K **LCE**-A19/E26, 80CRI, 4000K
	GU24 BASE, 120V **G13**-1 X 13W **G18**-1 X 18W **G26**-1 X 27W	**W**-White **B**- Black	**ACRYLIC** **A**-Clear Textured **POLYCARBONATE** **C**-Clear Textured **POLYETHYLENE** **W**-White Textured	**L**-CFL, 2700K

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST **ESTIMATED FROM LED SOURCE

90CRI OPTIONS AVAILABLE - SEE PAGE 112 FOR DIMMER COMPATIBILITY

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.

Specifications subject to change without notice. Printed in U.S.A. © 2020 Inter-Global Inc.