


- Available in LED, Incandescent & GU24
- Fade & Rust Resistant Composite Construction
- Wall Mount Only
- UL Listed for Wet Locations
- Standard Pack QTY: 6

BUNGALOW

FP133



EXTENDS: 5 3/4"
HCMT: 2 3/8"



RoHS
compliant



EXAMPLE # FP133-I60-BCP

| STYLE # | LIGHT SOURCE | BODY | DIFFUSER | OPTIONS |
|---------|--------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|---------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| FP133 | EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR | W-White B-Black | ACRYLIC C-Clear Flemish | P-Photocell |
| | LE800 - 13W, 80 CRI >88 Lumens Per Watt** | W-1140lm 3000K C-1280lm 4000K | | |
| | INCANDESCENT, MEDIUM BASE, 120V I60-1 X 60W Max | W-White B-Black | ACRYLIC C-Clear Flemish | P-Photocell LED LAMP, 3 YEAR WARRANTY, DIMMABLE, ENERGY STAR LWE-A19/E26, 80CRI, 3000K LCE-A19/E26, 80CRI, 4000K |
| | GU24 BASE, 120V G13-1 X 13W G18-1 X 18W | W-White B-Black | ACRYLIC C-Clear Flemish | P-Photocell L-CFL, 2700K |

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE



Scan the QR code to the left to access the Energy Star qualified product list.

90CRI OPTIONS AVAILABLE - SEE PAGE 112 FOR DIMMER COMPATIBILITY

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.

For more information contact our sales department at 1-800-325-7364 or visit www.interglobal-inc.com