

- Available in LED, Incandescent & GU24
- Fade & Rust Resistant Composite Construction
- Wall Mount Only
- UL Listed for Wet Locations
- Standard Pack QTY: 6

## FITTER NECK POCKET



### EXAMPLE # FP103-LE800C-BCP

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
<b>FP103</b>	<b>EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR</b>	<b>W-White</b> <b>B- Black</b>	<b>ACRYLIC</b> <b>C-Clear Prism</b> <b>W-White</b>	<b>P-Photocell</b>
<b>FP106</b>	<b>LE800 - 13W, 80 CRI W-1140lm 3000K &gt;88 Lumens Per Watt** C-1280lm 4000K</b>			
<b>FP109</b>	<b>MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED ARRAY, 50,000 HRS L70* AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY L900 - 11.3W Power Input CRI 74 (TYP) &gt;80 Lumens Per Watt** C-912lm 4000K</b>	<b>W-White</b> <b>B- Black</b>	<b>ACRYLIC</b> <b>C-Clear Prism</b> <b>W-White</b>	N/A
	<b>INCANDESCENT, MEDIUM BASE, 120V I60-1 X 60W</b>	<b>W-White</b> <b>B- Black</b>	<b>POLYCARBONATE</b> <b>C-Clear Prism</b> <b>W-White</b>	<b>P-Photocell</b> <b>LED LAMP, 3 YEAR WARRANTY, DIMMABLE, ENERGY STAR</b> <b>LWE-A19/E26, 80CRI, 3000K</b> <b>LCE-A19/E26, 80CRI, 4000K</b>
	<b>GU24 BASE, 120V G13-1 X 13W G18-1 X 18W</b>	<b>W-White</b> <b>B- Black</b>	<b>ACRYLIC</b> <b>C-Clear Prism</b> <b>W-White</b>	<b>P-Photocell</b> <b>L-CFL, 2700K</b>



\*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

\*\*ESTIMATED FROM LED SOURCE

Scan the QR code to the left to access the Energy Star qualified product list.

**90CRI OPTIONS AVAILABLE - SEE PAGE 112 FOR DIMMER COMPATIBILITY**

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.