


- Available in LED, Incandescent & GU24
- Fade & Rust Resistant Composite Construction
- Wall Mount Only
- UL Listed for Wet Locations
- Standard Pack QTY: 6

FITTER NECK POCKET JELLY JAR



FP101

EXTENDS: 5 7/8"
HCMT: 2 3/8"



RoHS
compliant



EXAMPLE # FP101-I60-BG-PLWE

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FP101	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR LE800 - 13W, 80 CRI W -1140lm 3000K >88 Lumens Per Watt** C -1280lm 4000K	W -White B - Black	POLYCARBONATE C -Clear GLASS G - Clear	P -Photocell
	MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED ARRAY, 50,000 HRS L70* AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY L900 - 11.3W Power Input C -912lm 4000K CRI 74 (TYP) >80 Lumens Per Watt**	W -White B - Black	POLYCARBONATE C -Clear GLASS G - Clear	N/A
	INCANDESCENT, MEDIUM BASE, 120V I60-1 X 60W	W -White B - Black	POLYCARBONATE C -Clear GLASS G - Clear	P -Photocell LED LAMP, 3 YEAR WARRANTY, DIMMABLE, ENERGY STAR LWE-A19/E26, 80CRI, 3000K LCE-A19/E26, 80CRI, 4000K
	GU24 BASE, 120V G13-1 X 13W G18-1 X 18W	W -White B - Black	POLYCARBONATE C -Clear GLASS G - Clear	P -Photocell L -CFL, 2700K



*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE

Scan the QR code to the left to access the Energy Star qualified product list.

90CRI OPTIONS AVAILABLE - SEE PAGE 112 FOR DIMMER COMPATIBILITY

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.