

- o Available in LED, Incandescent & GU24
- o Fade & Rust Resistant Composite Construction
- o Knockouts for Conduit
- o Wall or Ceiling Mount
- o UL Listed for Wet Locations



EXAMPLE # FK395-LE1200C-BWM

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FK391 FK395	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR LE800 - 13W, 80 CRI >88 Lumens Per Watt** LE1200 - 14W, 80 CRI >102 Lumens Per Watt** LE1800 - 22W, 80 CRI >88 Lumens Per Watt**	W -White B - Black	POLYCARBONATE F -Frosted Prismatic W -White	M -Motion Sensor EB -Emergency Backup
	W -1140lm 3000K C -1280lm 4000K W -1430lm 3000K C -1500lm 4000K W -1950lm 3000K C -2130lm 4000K			
	MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY, ENERGY STAR L1800 - 22W Power Input CRI 74 (TYP) >82 Lumens Per Watt**	W -White B - Black	POLYCARBONATE F -Frosted Prismatic W -White	M -Motion Sensor EB -Emergency Backup
	W -1704lm 4000K C -1824lm 4000K			
	INCANDESCENT, MEDIUM BASE, 120V I240 -2 X 40W Max	W -White B - Black	POLYCARBONATE F -Frosted Prismatic W -White	LED LAMP, 3 YEAR WARRANTY DIMMABLE, ENERGY STAR LWE -A19/E26, 80CRI, 3000K LCE -A19/E26, 80CRI, 4000K
	GU24 BASE, 120V G13 -1 X 13W G213 -2 X 13W G18 -1 X 18W G218 -2 X 18W	W -White B -Black	POLYCARBONATE F -Frosted Prismatic W -White	L -CFL, 2700K



*DATA PER LM79/LM80/TM21 & IES FILES AVAILABLE UPON REQUEST **ESTIMATED FROM LED SOURCE
Scan the QR code to the left to access the Energy Star qualified product list.

90CRI OPTIONS AVAILABLE - SEE PAGE 112 FOR DIMMER COMPATIBILITY

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.