


- Available in LED, Incandescent & GU24
- Fade & Rust Resistant Composite Construction
- Ceiling Mount
- UL Listed for Damp Locations
- Standard Pack QTY: 6

RESIDENTIAL CENTURY - 10.25"



FC312



RoHS compliant



EXAMPLE # FC312-G13-BFL

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FC312	INCANDESCENT, MEDIUM BASE, 120V I260-2 X 60W	W-White B- Black	POLYPROPYLENE F-Frosted GLASS G-Clear	LED LAMP, 3 YEAR WARRANTY DIMMABLE, ENERGY STAR LWE-A19/E26, 80CRI, 3000K LCE-A19/E26, 80CRI, 4000K
	GU24 BASE, 120V G13-1 X 13W G213-2 X 13W G18-1 X 18W G218-2 X 18W G23-1 X 23W G223- 2 X 23W G26-1 X 27W	W-White B- Black	POLYPROPYLENE F-Frosted GLASS G-Clear	L-CFL, 2700K

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE



Scan the QR code to the left to access the Energy Star qualified product list.

SEE PAGE 112 FOR DIMMER COMPATIBILITY


Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.

- Available in LED & GU24
- Fade & Rust Resistant Composite Construction with Powder Coated Aluminum Base
- Ceiling Mount
- UL Listed for Damp Locations
- Standard Pack QTY: 6

COMMERCIAL CENTURY - 10.25"



FC322



EXAMPLE # FC322-G13-BFPL

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS	
FC322	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR	W -White B -Black	POLYPROPYLENE F -Frosted GLASS G -Clear	M -Motion Sensor P -Photocell	
	LE800 - 13W, 80 CRI >88 Lumens Per Watt**				W -1140lm 3000K C -1280lm 4000K
	LE1200 - 14W, 80 CRI >102 Lumens Per Watt**				W -1430lm 3000K C -1500lm 4000K
FC322	MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED ARRAY, 50,000 HRS L70* AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY, ENERGY STAR	W -White B -Black	POLYPROPYLENE F -Frosted GLASS G -Clear	M -Motion Sensor	
	L1800 - 22W Power Input CRI 74 (TYP) >82 Lumens Per Watt**				C -1824lm 4000K
FC322	GU24 BASE, 120V G13 -1 X 13W G213 - 2 X 13W G18 -1 X 18W G218 - 2 X 18W G26 -1 X 27W	W -White B -Black	POLYPROPYLENE F -Frosted GLASS G -Clear	P - Photocell L -CFL, 2700K	



*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST

**ESTIMATED FROM LED SOURCE

Scan the QR code to the left to access the Energy Star qualified product list.

90CRI OPTIONS AVAILABLE - SEE PAGE 112 FOR DIMMER COMPATIBILITY

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.