


- Available in LED
- Powder Coated Cast Aluminum
- Wall or Ceiling Mount
- Enclosed & Gasketed
- ETL Listed for Wet Locations (IP65)
- Standard Pack QTY: 6

LUNAR




FL372

H/CTR: 5.9"




FL371

10.20"



H/CTR: 5.9"



RoHS compliant



EXAMPLE # FL371-LE1200W-BWM

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FL371 FL372	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR***	W -White B - Black	POLYCARBONATE W -White	M -Motion Sensor EB -Emergency Backup
	LE1200 - 14W, 80 CRI >102 Lumens Per Watt**	W -1430lm 3000K C -1500lm 4000K		(options not available with LE2600)
	LE1800 - 22W, 80 CRI >88 Lumens Per Watt**	W -1950lm 3000K C -2130lm 4000K		
	LE2600 - 32W, 80 CRI >84 Lumens Per Watt**	W -2700lm 3000K C -2750lm 4000K		
	MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED ARRAY, 50,000 HRS L70* AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY, ENERGY STAR***	W -White B - Black	POLYCARBONATE W -White	M -Motion Sensor
	L1800 - 22W Power Input CRI 74 (TYP) >82 Lumens Per Watt**	W -1704lm 3000K C -1824lm 4000K		



*DATA PER LM79/LM80/TM21 & IES FILES AVAILABLE UPON REQUEST **ESTIMATED FROM LED SOURCE
 ***EXCLUDES LE2600 MODELS AND MODELS WITH MOTION SENSOR OR EMERGENCY BACKUP OPTIONS
 Scan the QR code to the left to access the Energy Star qualified product list.

90CRI OPTIONS AVAILABLE - SEE PAGE 112 FOR DIMMER COMPATIBILITY

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.