


- Available in LED & Incandescent
- White Powder Coated Aluminum
- Wall or Ceiling Mount
- UL Listed for Wet Locations
- Standard Pack QTY: 6

SENTINEL - SHORT & MEDIUM




FS112



EXTENDS: 4 1/4"
HCMT: 3 7/8"

FS113



EXTENDS: 4 1/2"
HCMT: 5 1/4"

EXAMPLE # FS112-I40-WF-LCE

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FS112 FS113	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR	W-White	ACRYLIC C-Clear F-Glare Reduced Frost Prismatic POLYCARBONATE P-Clear	N/A
	LE800 - 13W, 80 CRI >88 Lumens Per Watt** W-1140lm 3000K C-1280lm 4000K			
	INCANDESCENT, MEDIUM BASE, 120V I40-1 X 40W Max	W-White	ACRYLIC C-Clear F-Glare Reduced Frost Prismatic POLYCARBONATE P-Clear	LED LAMP, 3 YEAR WARRANTY DIMMABLE, ENERGY STAR LWE-A19/E26, 80CRI, 3000K LCE-A19/E26, 80CRI, 4000K

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST **ESTIMATED FROM LED SOURCE



Scan the QR code to the left to access the Energy Star qualified product list.

90CRI OPTIONS AVAILABLE - SEE PAGE 112 FOR DIMMER COMPATIBILITY

Fixtures available with custom packaging options, assembled or knocked down. MOQs apply.

For more information contact our sales department at 1-800-325-7364 or visit www.interglobal-inc.com