



FB155 | FB156 BRADFORD WALL

- Fade & Rust Resistant Composite Construction
- UL Listed for Wet Locations
- Wall Mount Only
- Mounting Hardware Included



EXAMPLE # FB156-LE800C-BFP

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FB155 FB156	DEDICATED 120V LED EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE LE800 - 13W, 80 CRI W-1140lm 3000K C-1280lm 4000K >88 Lumens Per Watt**	B-Black W-White	ACRYLIC C-Clear F-Frost	P-Photocell 120V only. See page 18 for details. S-Security Motion Sensor & Photocell Combo. 120V only. See page 14.
	INCANDESCENT 120V INCANDESCENT, MEDIUM BASE, 120V I60-1 X 60W Max			P-Photocell 120V only. See page 18 for details. S-Security Motion Sensor & Photocell Combo. 120V only. See page 14. LED LAMP, 3 YEAR WARRANTY, DIMMABLE LWE-A19/E26, 90CRI, 3000K LCE-A19/E26, 80CRI, 4000K

See page 122 for dimmer compatibility. Data per LM79/LM80/TM21 available upon request. **Estimated from LED source. Fixtures available with custom packaging options, assembled or knocked down. MOQS apply. Specification subject to change without notice.

